

CE Certificate 10mm Ultra Clear Tempered Glass Manufacturer

About Ultra Clear Tempered Glass

Ultra Clear Tempered glass, also Low Iron Toughened Glass, is fabricated by heating [ultra clear low iron glass](#) to over 600°C and cooling it rapidly, which locks the outer surfaces of the glass in a state of high compression, and the core or center of the glass in compensating tension. It is a safety glass which is used when strength, thermal resistance and safety are important considerations.

Ultra Clear Tempered Glass Characteristic

High Strength

The super white tempered glass performs well in resisting bending and hitting owing to its high strength which is about five times that of normal float glass. It is able to withstand a surface pressure of 95Mpa.

High Safety

When the tempered glass is broken, it turns into alveolate granules with obtuse angles, which guarantee safety to make sure human harmless, and the toughening process greatly reduces the risk of thermal breakage to ensure less loss.

Heat Stability

The tempered glass is capable of withstanding a temperature change of 250 to 320°C while normal annealed glass can only bear 20 to 100°C.

High Transparency

Super high transparency and a neutral color making it the ideal glass where high visibility and clarity are required.

Performance Comparison

Items	Tempered Glass	Semi-tempered Glass	Normal annealed glass
Safety	Best	General	None
Intensity	152Mpa	/	30-90Mpa

Thermal Stability	250-320°C	100°C	20-100°C
Surface Stress	95Mpa	24-69Mpa	/
Broken State	Obtuse-angle grain	Shooting-broken	Sharp

10mm Ultra Clear Tempered Glass Specification

10mm ultra clear toughened glass available size: Maximum 3000*8000mm, Minimum 150*300mm

All the processing done on the 10mm super clear toughened glass like polish edges, cut to size, drill holes, cut notches, cutouts, screen printing, acid etched, etc. must be done before tempering.

Edge work

Any edges could be done perfectly on 10mm ultra clear toughened glass, like flat polished edge (T edge), pencil edge (C edge), beveled edge, ogee edge, matt edge, corner round edge.

Holes and notches

Tempered glass can be supplied with drilled holes (no matter straight or conical) and cut notches. We will consider hole and notch locations and size according to your drawings. Please kindly check below details:

Glass edge to nearest point of hole	10mm clear toughened glass should not have holes located any closer than 2 times the thickness of the glass.
Glass corner to nearest point of hole	Holes should not be located any closer than 6.5 times the thickness of the 10mm clear toughened glass.
Dimension of holes	The minimum dimension of a hole should not be less than the thickness of the glass. The maximum dimension of the hole should not be more than 1/3 the narrowest dimension of the piece.
Notches and cutouts	All must have a fillet with radius equal to, or greater than the thickness of the glass.

Shapes

Except rectangle 10mm ultra clear toughened glass, Jimmy Glass also could do shape 12mm ultra clear toughened glass, like round low iron hardened glass, Trapezoid super white reinforced glass, parallel ultra clear safety glass, etc.

10mm Ultra Clear Tempered Glass Application

Most often use as safety railing glass, high transparency aquarium glass, store front wall glass, kitchen

splashback glass, etc., and use to make [21.52mm low iron laminated glass](#) to use as security stair railing glass, jumbo size balcony glass, elevator glass, etc., and make 10+10+10mm anti-slip laminated glass for floor, etc.

Quality Standard

In accordance with EN12150 European tempered glass standard

In accordance with ASTM1048 American Standard

In accordance with GB 9963-1998 Tempered Glass Standard

In accordance with GB 17981-1999 Chinese Standard Tempered and Heat-Strengthened Glass

Pass Chinese Safety Glass Compulsory Certification (CCC), IGCC, CSI.


Tempered Glass Processing



Difference Between Normal Clear Tempered Glass and Low Iron Tempered Glass



Toughened Glass Furnace and Production Process



Toughened Glass Strong Wooden Crate Packing and Safety Loading

