□□□ 6 □□□□ □□□□□ □□□□ □□□□□ □□□□□ □□□□□□□□

□□□□□ □□□□□

6mm □□□□ □□□□ □□inted □□□□□ □□□□□ □□ □□□ 6 □□□□ □□□□ □□ □□□□□□□ □□□□, □□ □□□□□□□ □□□□□ □□□ □□□□□□ □□□□□□□ □□□□ □□ □□□ 6 □□□□ □□□□□ □□□□□ □□□□, □□ □□□ □□ □□□□□ □□□□□ □□□□□□□ □□ □□□□□ □□□□ □□□□□□□ □□□□□□ □□ □□□□□□□ □□□□ □□ □□□ □□ □□□ □□□ □□□□, □□□□, □□□□□ □□ □□□□ . □□ □□□□□□□ □□□□□ □□□ □□□□ □□□□□ □□ □□□□□, □□□□□ □□□ □□□□□□ □□□ □□□□□ □□□□□ □□□ □□ □□□□ □□□ □□ □□□□ □□□□□□□ □□ □□□ □□□ □□□, □□□□ □□ □□ □□□□ □□ □□□ □□□□□□□ □□□□ □□□ □□□

□□□□□ □□□□ □□inted □□□□□ □□□□□ □□□ □□□□□ □□ □□□□□□□ □□□□ □□□□ □□□□□□□□ □□ □□□□□□□ □□□□ □□ □□ □□□ □□□ □□□□ □□ □□□□□□□ □□□□□ □□ □□□ □□□ □□□□□□□□ □□□□ □□□□ □□□ □□ □□□□□□□□ □□ □□□□□□□ □□□□□ □□ □□□□ □□ □□□ □□□□ □□ □□□□ □□□ □□□□□□□□ □□□□□ □□□□ □□□□□ □□ □□□□ □□ □□□ toughened □□□□ □□ □□□□ □□ □□□ □□ □□□□□□□□ □□□□ □□□□ □□□□ thermally □□ □□ □□□□ □□□

□□□□ □□□□ □□inted □□□ □□□□□ □□□□□ □□□□□ □□□ □□□□□□□ □□□□ □□ □□□□, □□□□□□, □□□□□□ □□□□□□ □□□, □□□□□□□□□ □□□□□ □□ □□□□□□□□□ □□□□□, □□□□

6 □□□□ □□□□□ □□□□ □□□□ □□□ □□□□□ □□enefits:

□□□□□ □□ □□□ □□ □□□ □□□□□ □□□□□ □□ □□ □□□□□ □□□□□ □□□□□□ □□ □□□□□□ □□ □□□□□□ □□□□□□

□□□□ □□□□□ □□□□ □□ □□□□□ □□ □□□□□ □□□ □□□ □□□□□ □□ □□□□□□

□□□□□□□□□□ □□□□□ □□□□□□□□□□ □□ □□□□□□□□ □□□□ □□ □□□

□□□□ □□□ □□□□□ □□□□□ □□ □□□□□□□□□□**:**

□□□□□ **42x52 □□□:**

□□□□□ □□□□/□□□□□ □□□□, □□□□ □□□□ □□□

□□□□ □□□□ / □□□□□□ □□□□, □□□□□ □□□□

□□□□ □□□□□□ / □□□□□□ □□□□□□, □□□□□□ □□□□, □□□□□□ □□□□□□ □□□

□□□□□□ □□□□□ / □□□□ □□□□□, □□□□□ □□□□□

□□□□ □□ □□□□□:

4 □□□□, 5 □□□□, 6 □□□□, 8 □□□□, 10 □□□□

□□□□□ □□□□:

2140x1650mm, 2140x3300mm, 1830 * 2440 □□□□, 2140 * 3660 □□□□

□□□□□ □□□□ □□□□ □□□ □□□□□ □□□□□□□□□□:

Windows, □□□□□□, shopfronts □□□□□□□□□, □□□□□□□□, □□, □□□ □□ □□□□□ □□□□□

□□□□□□ □□□□□ □□□□□□□□, □□□□□□□, □□□□□□□ / balustrades, □□□

□□□□□□□□□ windows □□ □□□□□, □□□□□□□□□, □□□□□□□□□ □□□□□□□□□□, □□□

□□□□□□□□, □□□□ □□□, □□□

□□□□□ □□□□ □□□ □□□□□□□ □□□ □□□□□ □□□□□ □□□□□□□□□ □□□□ □□□□□:

Tinted Float Glass Performance Data

Color	Thickness	Visible Light Transmittance	Visible Light Reflectance	UV Light Transmittance	Direct Sunlight Transmittance	Direct Sunlight Reflectance	Total Solar Transmittance	shading coefficient (SC)	SHGC	K Value (Summer Daytime)	K Value (Winter Night)
Euro Bronze	5mm	51.94%	6.44%	14.52%	51.78%	6.69%	62.50%	0.70	0.84	5.640	5.272
	6mm	47.15%	6.73%	11.83%	46.87%	6.79%	58.83%	0.66	0.83	5.606	5.243
Euro Grey	5mm	51.66%	6.36%	20.29%	49.19%	6.48%	60.63%	0.68	0.84	5.623	5.272
	6mm	45.24%	6.06%	16.47%	42.98%	6.15%	56.11%	0.63	0.84	5.582	5.243
Dark Grey	5mm	47.90%	6.77%	19.87%	46.96%	6.75%	58.91%	0.66	0.84	5.606	5.272
	6mm	41.96%	6.59%	16.54%	41.37%	6.53%	54.82%	0.62	0.83	5.569	5.243
Light Blue	5mm	71.07%	7.78%	26.60%	53.99%	6.94%	64.07%	0.72	0.654	5.272	5.843
	6mm	67.74%	7.69%	24.13%	50.67%	6.96%	61.61%	0.69	0.632	5.243	5.808
F-Green	5mm	74.60%	8.03%	24.54%	48.75%	6.67%	60.26%	0.68	0.619	5.272	5.843
	6mm	71.36%	7.66%	20.22%	43.72%	6.35%	56.60%	0.64	0.586	5.243	5.808

For reference only

6mm [redacted]**:**

6 [illegible] [illegible] [illegible]

6 □□□□ □□□□□ □□□□ □□□□□□□ □□□□ □□□□□□: