

High performance and CE standard acid etched frosted satin surface colored pvb tempered laminated glass for decorative effects

Satin surface processed color [pvb tempered laminated glass](#), also called [acid etched glass](#) processed color pvb tempered laminated glass or frosted processed color pvb tempered laminated glass, which select good quality float glass at first, frosted processing, tempering, then laminating, make sure durable, good appearance in building projects.

How satin surface pvb tempered laminated glass production?

1.We will select high quality float glass as raw materials, cutting, edging, then acid etched glass, make sure the surface texture uniform and flat, the tempering and laminating processing will be better and easier.



2.Use professional test instrument to inspect tempered glass pressure, and whether have Impurities in it, make sure its self explosion rate in less than industry standard



3. When laminated processing, make sure the temperature is 15-25 Celsius, humidity 20-28%, use ruler check the two layers of glass whether flush



Some our finished frosted surface color pvb tempered laminated glass products photo share:



This kind of decorative glass is a good choice which widely use different building projects, makes building beautiful and modern.



Specification of Satin surface color pvb tempered laminated glass

Available thickness	6+6mm, 8+8mm, 10+10mm, 1/2, 5/8, 3/4
Available size	Flat shape reach maximum 3300*8000mm, minimum radius of curved shape reach 600mm, size reach 2440*5500mm
Color choice	Red, yellow, blue, green, black, white, support customized based on color pantone
Features	Decorative, privacy, high safety, noise reduction, heat reduction
Delivery time	15-20 working days when drawing and order confirm
Packages	Brand new high safety strong plywood crates, with corks separate glass, and outside fully cover plastic film

Why choose us and our laminated glass products?

- 1) Select grade A float glass with no chips zero bubbles, zero scratches and perfect flat surface performance.
- 2) Our own advanced temper machine to guarantee our tempered laminated spider glass quality, with splendid temper stress uniformity, the self explosion rate reduce to 0.1%, or closed to 1/10000 even Zero when use low iron float glass tempered after heat soak test, and laminate machine will make sure edge alignment between laminates smaller than 2mm, 100% zero delaminate.
- 3) Much strict quality control according to ISO9001, make sure accurate size, thickness, and process works when delivery
- 4) Use brand new customized strong plywood crates with corks separate and plastic film fully covered outside to guarantee loading safety and avoid breaking when sea transportation.
- 5) Provide one stop service, like supply high quality glass fittings like one side 304 material stainless steel spider fittings, two side 304 material stainless steel spider fittings, four side 304 material stainless steel spider fittings for durable use and convenient installation.