

A 5 mm

□ □ □ □ □ □ □ □ □ □

[illegible]

5 mm Colores ☐☐☐☐ ☐☐☐☐☐

- 89% 的受訪者認為「香港人」是「中國人」
- 89% 的受訪者認為「中國人」是「香港人」
- 89% 的受訪者認為「中國人」是「中國人」
- 89% 的受訪者認為「中國人」是「中國人」

5 mm □□□□□ □□□□□□□□□□

1650x2140mm □ 1650x2200mm □ 1830x2440mm □
1830x2600mm □ 2600x3660mm □ 2140x3300mm □ 2140x3660mm □ 2250x3300mm □ 2250x3660mm □
2440x3300mm □ 2440x3660mm □

5 mm □□□□ □□□ □□□□□□□□

5 mm

□ □ □ □ □ □ □ □ □ □ □ □ □ □

GB11614; BS EN572 2 ASTM C 1036

CLEAR FLOAT GLASS TECHNICAL DATA

mm	(kg/m2)	Visible Light %		Solar Radiant Heat %				Shading Coefficient (s.c)	U Value (W / M2)	Sound Insulation (dB)
		Transmission	Reflectivity	Direct Penetrate	Reflectivity	Absorb	Total Penetrate			
2	5	91	8	87	8	5	88	1.01	5.9	*
3	7.5	90	8	85	8	7	87	1	5.8	30
4	10	90	8	83	8	9	85	0.98	5.8	30
5	12.5	89	8	81	7	12	84	0.97	5.7	31
6	15	89	8	80	7	13	83	0.95	5.7	31
8	20	88	8	76	7	17	81	0.93	5.7	33
10	25	87	8	73	7	20	79	0.91	5.6	35
12	30	86	8	71	7	22	77	0.89	5.6	36
15	37.5	85	8	66	7	27	73	0.84	5.4	38
19	47.5	84	8	62	7	31	70	0.81	5.3	40

for reference only.

0000000 00000



0000000 0000000



□□□□□□ □□□□□□□□□□□□

